




TMCX



TMCX Globally Approved, Hazardous (Classified) Location Barrier Cable Gland

For MC, MC-HL, Interlocked & Teck Armored Cables

- Simple, sequential installation process
- Compound barrier type flameproof seal
- Integral protected deluge seal
- 360° grounding spring (non-magnetic)
- Disconnectable, union design feature
- -76°F to 185°F / -60°C to 85°C
- Globally marked, UL, cCSAus, IECEx & ATEX



TECHNICAL DATA

Design Specification	BS 6121:Part 1:1989, IEC 62444, EN 62444
Mechanical Classification	Impact = Level 8, Cable Anchorage = Class D
Enclosure Protection	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel only
ATEX Certificate	SIRA07ATEX1122X
Code of Protection	II 2GD, Ex d IIC, Ex e IIC, Ex tD A21 IP66
Compliance Standards	EN 60079-0,7, EN 612410,1
IECEx Certificate	IECEx SIR 07.0083X
Code of Protection	Ex d IIC, Ex e II, Ex tD A21 IP66
Compliance Standards	IEC 60079-0,1,7,31
cCSAus Certificate	1129339
CSAus Code of Protection	Class I, Div 1 and 2, Groups A, B, C and D; Class II, Div 1 and 2, Groups E, F, and G; Class III, Div 1 and 2; Encl. Type 3, 4, 4X. Class I, Zone 1, AEx d IIC; AEx e II
cCSA Code of Protection	Class I, Div 1 and 2, Groups A, B, C and D; Class II, Div 1 and 2, Groups E, F, and G; Class III, Div 1 and 2; Encl. Type 3, 4, 4X. Ex d IIC; Ex e II:
Compliance Standards	CAN/CSA-C22.2 Various Sections (See Certificate) CAN/CSA-E60079-0, CAN/CSA-E60079-1
UL Certificate	E256366
Code of Protection	Class I, Div 2, Groups A,B,C,D, Class II, Div 2, Groups F,G Class I, Zone 1, AEx d IIC, AEx e II
EAC Certificate	TC RU C-GB.AA87.B.00487
UkrSEPRO	UA.TR.047.C.0644-15
CCOE / PESO (India) Certificate	P333688
RETIE Approval Number	03866
Marine Approvals	LRS:01/00172 (E3) DNV: TAE00000Y ABS: 14-LD234401A-4-PDA BV: 43180/A1
Ingress Protection Rating**	NEMA 4X & IP66
Cable Type	Corrugated & Interlocked Metal Clad Armor (MC) or TECK90, Continuously Welded Metal Clad Armor (MCHL), ACIC-HL, ACWU90-HL, RC90-HL, RA90-HL
Armor Clamping	360° Stainless Steel Grounding Spring (non-magnetic)
Jacket Sealing Technique	CMP Unique Displacement Seal Concept
Sealing Area(s)	Inner Compound Barrier and Cable Outer Jacket
Seal Material	CMP SOLO LSF Halogen Free Thermoset Elastomer / Epoxy Barrier Compound
Cable Gland Material	Copper Free (<0.4%) Aluminum, Stainless Steel, Electroless Nickel Plated Brass

Cable Gland Selection Table

Refer to illustration at the top of the page

* Mechanical & Electrical Classifications applied as per IEC 62444 & EN 62444

** When CMP installation accessories are used. Refer to page 7 or www.cmp-products.com for further information.

Order Reference (NPT)			Entry Thread "C"	Entry Thread "C"	Minimum Thread Length "E"	Minimum Thread Length "E"	Cable Armor Diameter "A"				Cable Jacket Diameter "B"		Nominal Assembly Length "F"	Max		Shroud	Weight (Ozs)
Aluminum	Nickel Plated Brass	Stainless Steel	NPT	Metric	NPT	Metric	Armor Stop in		Armor Stop Out		Min	Max		Across Flats "D"	Across Corners "D"		
							Min	Max	Min	Max							
TMCX050SA	TMCX050SNB	TMCX050SSS	½"	M20	0.78	0.59	No Stop	No Stop	0.34	0.50	0.35	0.55	1.83	1.20	1.32	PVC06	7.90
TMCX050A	TMCX050NB	TMCX050SS	½"	M20	0.78	0.59	No Stop	No Stop	0.51	0.67	0.55	0.79	2.06	1.42	1.56	PVC09	9.91
TMCX075A	TMCX075NB	TMCX075SS	¾"	M25	0.80	0.59	0.59	0.76	0.76	0.92	0.67	1.04	2.09	1.61	1.78	PVC10	11.61
TMCX100A	TMCX100NB	TMCX100SS	1"	M32	0.98	0.59	0.78	0.97	0.97	1.15	0.91	1.27	2.24	1.97	2.17	PVC13	17.53
TMCX125A	TMCX125NB	TMCX125SS	1 ¼"	M40	1.01	0.59	1.08	1.23	1.23	1.39	1.16	1.50	2.22	2.17	2.38	PVC15	20.92
TMCX150A	TMCX150NB	TMCX150SS	1 ½"	M50	1.03	0.59	1.32	1.46	1.46	1.62	1.40	1.74	2.31	2.36	2.60	PVC18	24.45
TMCX200SA	TMCX200SNB	TMCX200SSS	2"	M50	1.06	0.59	1.51	1.68	1.68	1.85	1.58	1.97	2.52	2.76	3.03	PVC21	42.33
TMCX200A	TMCX200NB	TMCX200SS	2"	M63	1.06	0.59	1.77	1.93	1.93	2.09	1.86	2.21	2.49	2.95	3.25	PVC23	38.80
TMCX250SA	TMCX250SNB	TMCX250SSS	2 ½"	M75	1.57	0.59	2.05	2.16	2.16	2.32	2.08	2.44	2.73	3.15	3.47	PVC25	59.97
TMCX250A	TMCX250NB	TMCX250SS	2 ½"	M75	1.57	0.59	2.25	2.41	2.41	2.55	2.33	2.68	2.84	3.35	3.68	PVC27	56.48
TMCX300A	TMCX300NB	TMCX300SS	3"	M90	1.63	0.95	2.54	2.78	2.78	2.97	2.62	3.13	3.87	4.33	4.76	LSF32	123.46
TMCX350A	TMCX350NB	TMCX350SS	3 ½"	M100	1.69	0.95	2.91	3.29	3.29	3.49	2.99	3.83	4.52	5.25	5.78	LSF34	236.34
TMCX400A	TMCX400NB	TMCX400SS	4"	M115	1.73	0.95	2.91	3.29	3.29	3.49	2.99	3.83	4.52	5.25	5.78	LSF34	264.55

Order Code Example: TMCX250SS "TMC" (Gland Type) - "250" (2 ½" NPT Thread) - "SS" (Material Stainless Steel)

Dimensions are displayed in inches unless otherwise stated